

Torishima Pump Global Network



East Asia

1 Torishima Pump Mfg. Co., Ltd. ■ ■
1-1-8 Miyata-cho, Takatsuki-city, Osaka 569-8660 Japan
Tel : +81-72-690-2308 / Fax : +81-72-690-2329

2 Kyushu Torishima Co., Ltd. ■
9857-13, Ohaza Kawako, Wakagi-cho, Takeo-city,
Saga 840-0813 Japan
Tel : +81-954-26-3081 / Fax : +81-954-26-3080

3 Torishima Pump Mfg. Co., Ltd.
Beijing Office
Rm707, Building 1, KUNSHA CENTER,
No.16 Xinyuanli, Chaoyang District,
Beijing, P.R.China PC:100027
Tel : +86-10-84682891 / Fax : +86-10-84682890

4 Torishima Pump (Tianjin) Co., Ltd. ■
No.9 Gaoxin Road, Wuqing Development Zone,
Tianjin, P.R.China PC:301700
Tel : +86-22-59695601 / Fax : +86-22-59695609

5 Torishima (Hong Kong) Ltd. ■ ■
Unit A, 21/F., Tower A, Billion Centre,
1 Wang Kwong Road, Kowloon Bay, Kowloon,
Hong Kong
Tel : +852-2795-1838 / Fax : +852-2754-3293

South East Asia

6 Torishima (Hong Kong) Ltd.
Vietnam Office
No.76 Bui Thi Xuan Street, Hai Ba Trung District,
Hanoi, Socialist Republic of Vietnam
Tel : +84-4-943-7880 / Fax : +84-4-943-7876

7 Torishima Pump Mfg. Co., Ltd.
Singapore Office
82 Toh Guan Road East, #C2-14-4 WaterHub,
Singapore 608576
Tel : +65-6779-0123 / Fax : +65-6779-6900

8 Torishima Service Solutions
Asia Pte. Ltd. ■
48, Toh Guan Road East, #02-142,
Enterprise Hub, Singapore 608586
Tel : +65-6933-8772 / Fax : +65-6933-8777

9 P.T. Torishima Guna Engineering ■
10 P.T. Torishima Guna Indonesia ■
Jalan Rawa Sumur Timur No.1 Pulogadung
Industrial Estate, P.O.Box 1160, Jakarta, Indonesia
Tel : +62-21-460-3963 / Fax : +62-21-460-3937

11 P.T. Geteka Founindo ■
JL Pulo Ayang Kav. AA2 Pulogadung Industrial
Estate, P.O.Box 1160 JAT, Jakarta 13011 Indonesia
Tel : +62-21-460-3963 / Fax : +62-21-460-3937

South Asia

12 Torishima Pumps India Pvt. Ltd.
302 & 302A, 3rd Floor, Tower-B, Millennium Tower,
Sector27, Gurgaon-122002, Haryana, India
Tel : +91-124-4728960 / Fax : +91-124-4728950

13 Torishima Pumps India Pvt. Ltd.
Service Division ■
Plot No. 27 B, C, D, Hoskote KIADB Industrial Area,
Chokkahalli Village, Kasaba Hobli, Hoskote Taluk,
Bangalore-562114, Karnataka, India
Tel : +91-80-39581000 / Fax : +91-80-39581010

Oceania

14 Torishima Australia Pty. Ltd.
643-645 Glenhuntly Road,
Caulfield South VIC 3162 Australia
Tel : +61-3-9523-7998

Middle East

15 Torishima Service Solutions FZCO ■
Plot of Land TP010501 Techno Park-Jebel Ali,
PO Box. 37603 Dubai, U.A.E.
Tel : +971-4-880-7344 / Fax : +971-4-880-7354

16 Torishima Pump Mfg. Co., Ltd.
Middle East Office
Office No.901, Deluxe Tower, Delma Street,
Al Nahyan Camp Area, P.O.Box 53567,
Abu Dhabi, U.A.E.
Tel : +971-2-674-3880 / Fax : +971-2-674-3881

17 Torishima Pump Mfg. Co., Ltd.
Qatar Project Office
Office No.11,1st Floor, West Corner Centre,
Salwa Road-Midmac R/A,
P.O.Box 37027 Doha, Qatar
Tel : +974-4450-6915 / Fax : +974-4450-6916

18 Torishima Pump Mfg.Co.,Ltd.
Saudi Arabia Office
Al Riyadh, Al Khair Plaza, Office No.2
Al Amir Muhd IBN A.A. Road, Althalea
SP-643351929, Kingdom of Saudi Arabia
Tel : +966-11-2931366

Europe

19 Torishima Europe Ltd.
2 Colliery Gate, Clyde Gateway East, Glasgow
G32 8RH Scotland, UK
Tel : +44-1236-443951 / Fax : +44-1236-702875

20 Torishima Service Solutions
Europe Ltd. ■
2 Colliery Gate, Clyde Gateway East, Glasgow
G32 8RH Scotland, UK
Tel : +44-1236-442390 / Fax : +44-1236-702875

21 Torishima Europe Projects Ltd.
Torishima House, Brook Lane, Westbury,
Wiltshire BA13 4ES England, UK
Tel : +44-1373-858143

22 Torishima Europe Ltd. Madrid Office
Avda, Fuente Nueva 12, 28703
San Sebastian de los Reyes, Madrid, Spain
Tel : +34-91-002-7541 / Fax : +34-91-284-6901

23 Torishima Europe Ltd. Poland Office
ul. Pomianowska 7, 03-136 Warszawa, Poland
Tel : +48-604-557-137

North America

24 Torishima Pump Mfg. Co., Ltd.
North America East Office
100 Grove Street, Suite 217, Worcester
MA 01605-2654 U.S.A.
Tel : +1-508-753-6600 / Fax : +1-508-753-8276

Central America

25 Torishima Europe Ltd. Mexico Office
Av Paseo de La Reforma 350,11th floor,
Juárez,Cuauhtémoc, 06600
Ciudad de México,D.F., México
Tel : +52-55-9171-1426 / Fax : +52-55-9171-1499

CAL (Cast Iron)

CAR (Stainless Steel)

End-Suction Volute Pump



Go Green with The Eco-Pumps




CAL: Cast Iron
CAR: Stainless Steel
(10bar)

Energy Saving	- High-Efficiency Pump - Impeller Trimmed to Exactly Meet Customer Specification - Ultra High Efficiency Motor (Equivalent to IEC IE3)
Downsizing	Higher Speed Enables Same Duty to be Achieved with Smaller Pump
Easy Maintenance	- Simple Maintenance with Mechanical Seals - Excellent Parts Interchangeability - Back Pull-Out Design
Convenience	- Low NPSH (High Suction Performance) - Stable Operation
Safety	Shaft Guard and Totally Enclosed Coupling Guard


Optimized Hydraulic Performance

CFD (Computational Fluid Dynamics) optimized casing design ensures smooth fluid flow.




3D High-Efficiency Impeller

Three dimensional curved impeller optimizes smooth fluid flow.




Meeting Customer's Specification (Impeller cut)

The impeller diameter can be cut to meet the customer's specification to reduce unnecessary power consumption.



Defined Size doesn't match customer's specific duty resulting in unnecessary power consumption

Impeller Cut Meet's customer's specific duty to optimize power consumption




TU Motor (Torishima Ultra High Efficiency Motor)

IEC (International Electrotechnical Commission) classifies IE1 (standard), IE2 (high efficiency), IE3 (premium efficiency) by motor efficiency. TU motor is equivalent to IE3.


- Iron losses are reduced** by use of high quality magnetic steel sheet.
- Copper losses are reduced** by coil combination and optimized iron core configuration.
- Mechanical losses are reduced** by downsized fan.
- Reduced noise**

Motors of the following power output are in regular stock.
2P: 0.75kW to 22kW
4P: 0.75kW to 55kW




Mechanical Seal as Standard

Standard mechanical seal (rubber bellows type) is easy to install and does not damage shaft, thus eliminating need for shaft sleeve. Minimal leakage from seal improves cleanliness around pump.



Low NPSH / Stable Operation



Enhanced Safety with Shaft Guard and Totally Enclosed Coupling Guard

The Eco-Pumps (CAL/CAR) are equipped with a shaft guard and totally enclosed coupling guard. A totally enclosed coupling guard improves safety and maintenance compared to an existing coupling guard due to the wide area of coverage.

Existing Pump with Standard Coupling Guard and No Shaft Guard



Totally Enclosed Coupling Guard and Shaft Guard



Shaft Guard



Totally Enclosed Coupling Guard

All CAL/CAR series pumps are equipped with shaft guard.

Applied condition of enclosed coupling guards:
TU motor: 2P-55kW or less, 4P-110kW or less
Coupling diameter: 280mm or less
Motor size and frame depends on manufacturer selected.

Higher Speed Enables Pump Size to be Reduced

Increasing the pump speed by using a 2 pole motor reduces the pump size and weight.


Conditions: total head of 50m, capacity of 1m³/min, 60Hz

Pole number: 4P
Pump size: CAL80-400
Motor output: 18.5kW
Weight: **400kg**

Pole number: 2P
Pump size: CAL50-200
Motor output: 15kW
Weight: **209kg**

Weight reduced by 47% compared to 4P!

$$= (400 - 209) \div 400 \times 100$$



The above diagram describes characteristics of 2P. We can provide the design for 4P as well. Weight includes pump, base plate, motor and coupling. Motor weight differs depending on manufacturer.


Applications

Utility	Co-generation	Cooling water pump, Hot water (circulation) pump
	Air conditioning	Cold water pump, Cooling water pump, Hot water pump
	Drainage treatment	Raw water pump, Filtrate pump, Back wash pump, Transfer pump
	Pure water facility	Raw water pump, RO wash pump, Recovering back wash pump, Filtrate water pump
Iron and Metal	Power generation	Deaerator feed water pump
	Hot rolling	Transfer pump, Hot water pump, Water pumping pump, Filtrate pump, Back wash pump,
	Flue gas desulfurization	Cooling water pump, Industrial water pump
	Roll coolant	Spray pump
	Plating	Wash pump (Rinse pump)
Food and Beverage	Manufacturing process	Cold water pump, Cooling water pump (Circulation / Boost), Recycle water pump, Filtrate pump, Sprinkling pump
	Refrigerator	Chilled pump, Defrost pump
	CIP system	CIP supply / return pump
Automobile (Painting plant)	Degreasing process	Degreasing pump, Hot / Cold water wash pump, Spray pump
	Transformation process	Chemical pump, Hot / Cold water wash pump, Pure water pump
	Electrodeposition process	Electrodeposition liquid circulation pump, Wash pump, Pure water pump
Garbage incinerating plant	Power generation	Deaerator feed water pump, Condensate pump,
	Heat decrease tower	Heat decrease pump, Spray pump for heat decrease tower
	Drainage	Reuse water pump (pumping, transferring, feeding)
Other liquid handled	Brain, Acetone, Calcium chloride, Kalium chloride, Alkaline solution, Ethylene glycol, Agua fortis, Sulfate, Sodium hydroxide, Ammonia liquor, Caustic soda, etc. <i>Please ask about special fluid.</i>	

Specification

		CAL (Cast Iron) 	CAR (Stainless Steel) 
Handled liquid	Kinds	Clean water, Warm water, Oil, Chemical medicine, Alkaline solution, Brine, Heat transfer media, Abrasive slurry liquid under 3wt%, etc.	Pure water, Hot water, Sea water, Salted water, Refrigerant, Electrodeposition paint, Abrasive slurry liquid under 3wt%, etc.
	Temperature	Standard: -10°C to +80°C Option: -30°C to +350°C	Standard: -10°C to +80°C Option: -40°C to +140°C
Max. discharge pressure		Standard: 1MPa (10kgf/cm ² G) Option: 1.4MPa (14kgf/cm ² G)	1MPa (10kgf/cm ² G)
Max. suction pressure		0.8MPa (8kgf/cm ² G)	0.8MPa (8kgf/cm ² G)
Design	Impeller	Closed	Closed
	Shaft seals	Standard: Single mechanical seal (Rubber bellows) Option: Double mechanical seal, Gland packing	Standard: Single mechanical seal (Rubber bellows) Option: Double mechanical seal, Gland packing
	Water injection for bearing	Standard: Internal injection Option: Quenching, Flushing	Standard: Internal injection Option: Quenching, Flushing
	Lubricated bearing	Standard: Grease lubrication Option: Oil lubrication	Standard: Grease lubrication Option: Oil lubrication
Flange standard, Suction / Discharge direction		JIS 10K R.F. Shaft direction suction / Vertical top discharge	JIS 10K R.F. Shaft direction suction / Vertical top discharge
Pump material	Casing	Standard: FC250 Option: FCD400	Standard: SCS13 Option: SCS14
	Impeller	Standard: FC200 Option: SCS13	Standard: SCS13 Option: SCS14
	Shaft	Standard: SUS420J2 Option: SUS329J1+S45C, SUS304	Standard: SUS304 Option: SUS316, SUS329J1+S45C
	Case wear ring	Standard: PSG Option: SUS304	—

Design Features



Parts Interchangeability

■ **2P type** Same color and number in the same parts indicate interchangeability.

Parts Pump type	Casing	Casing Cover	Bearing Housing	Shaft	Mechanical Seal
32-125	1	1	1	1	1
40-125	2				
65-125	3				
32-160	4	2			
40-160	5				
50-160	6				
32-200	7	3			
40-200	8				
50-200	9				
80-160	10	4	2	2	2
80-200	11	5	3	3	
32-250	12	6			
40-250	13				
50-250	14				
80-250	15	7			

■ **4P type** Same color and number in the same parts indicate interchangeability.


Parts	Casing	Casing Cover	Bearing Housing	Shaft	Mechanical Seal
Pump type					
32-125	1	1	1	1	1
40-125	2				
65-125	3				
32-160	4	2			
40-160	5				
50-160	6				
65-150	7	3			
32-200	8				
40-200	9				
50-200	10				
65-190	11				
80-150	12	2	2	2	
80-190	13				
100-190	14				
32-250	15				
40-250	16				
50-250	17				
65-240	18				
80-240	19				
100-245	20				
100-250	21				
50-315	22	8			
65-310	23				
80-310	24				
100-310	25	9			
150-190	26				
150-200	27				
125-240	28	10			
125-250	29				
200-240	30				
200-250	31	11			
125-310	32				
125-315	33				
80-400	34	12			
100-400	35				
125-400	36				
150-310	37	13			
150-315	38				
150-390	39				
150-400	40	14			

Pump Sectional Drawing

The basic structure is same between CAL and CAR for parts interchangeability. CAR, which is made from stainless, does not require case wear ring. Due to adopting build to order method, various combination with pump material, seal and bearing is available according to liquids kinds and temperature.

Sstandard


Seal: Mechanical seal
Bearing: Grease lubrication



Detail drawing of seal part

Option


Seal: Mechanical seal + Water cooling
Bearing: Oil lubrication



Detail drawing of seal part

Option


Seal: Double mechanical seal
Bearing: Oil lubrication



Detail drawing of seal part

Option

Seal: Gland packing
Bearing: Grease lubrication




Detail drawing of seal part


Parts number	Parts name	Parts number	Parts name	Parts number	Parts name	Parts number	Parts name
1020	Volute casing	3600.2	Bearing cover	4580	Lantern ring	9010	Hex. bolt
1610	Casing cover	4000.1	Flat gasket	4610	Gland packing	9041	Nock
1830	Support foot	4000.2	Flat gasket	4710	Seal cover	9130	Plug
2100	Shaft	4000.3	Flat gasket	5020.1	Casing wear ring	9233	Lock nut
2300	Impeller	4120.1	O-ring	5020.2	Casing wear ring	9400.1	Key
3210.1	Deep groove ball bearing	4230.1	Labyrinth ring	5070.1	Deflector	9400.2	Key
3210.2	Deep groove ball bearing	4230.2	Mechanical seal	5070.2	Deflector		
3300	Bearing housing	4330	Shaft box gland	5500	Washer		
3600.1	Bearing cover	4520		6430	Oil gauge		

CAL (Cast Iron) Selection Range Charts


50Hz-2P
(3000min⁻¹)




60Hz-2P
(3600min⁻¹)




50Hz-4P
(1500min⁻¹)




60Hz-4P
(1800min⁻¹)



50Hz-6P
(1000min⁻¹)




60Hz-6P
(1200min⁻¹)




CAR (Stainless Steel) Selection Range Charts


50Hz-2P
(3000min⁻¹)




60Hz-2P
(3600min⁻¹)




50Hz-4P
(1500min⁻¹)




60Hz-4P
(1800min⁻¹)



50Hz-6P
(1000min⁻¹)



60Hz-6P
(1200min⁻¹)



Dimension Table


- Flange standard CAL: JIS10K RF / CAR: JIS10K RF
- Dimension in the table is based on totally enclosed fan-cooled motor.
Note: Motor size and frame depends on manufacturer selected.
- */** in the table indicate that motor frame is the same but shaft diameter (d2) is different.
- Base plate material FC: Cast Iron SS: Steel
Option: FC (Cast Iron) can be replaced with SS (Steel).



FC Base Plate



SS Base Plate



The above dimension is for SS (Steel) base plate.
FC (Cast Iron) base plate follows above.

Dimension Table for 2P Motor Drive

Pump Sizes	Pump									Motor			Base Plate				Foundation Dimensions								Coupling		Refer.			
	Bore		Dimension				Axle	Weight		Frame	Dimension																			
	DN1	DN2	a	f	h1	h2	d1	Grade	Grade		R	d2	Mate- rial	b3	I3	A	Wt.	h3	i	b2	I2	M	N	P	Q	V1	V2	t	Wt.	TL
	mm	mm	mm	mm	mm	mm	mm	L	R		kg	kg	---	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
32-125 40-125	50 65	32 40	80 80	360 360	112 112	140 140	24 24	27 28	28 29	71M	120	14	FC	370	740	0	19.2	157	30	330	550	200	50	4	M12	95	95	3	1.1	681
										80	140	19	FC	370	740	0	18.9	157	30	330	550	200	50	4	M12	95	95	3	1.1	725.5
										80M	140	19	FC	370	740	0	18.9	157	30	330	550	200	50	4	M12	95	95	3	1.1	705
										90S	156	24	FC	370	740	0	18.1	157	30	330	550	200	50	4	M12	95	95	3	1.1	750.5
										90L	168.5	24	FC	370	740	0	18.1	157	30	330	550	200	50	4	M12	95	95	3	1.1	775.5
										100L	193	28	FC	370	740	0	18.5	157	30	330	550	200	50	4	M12	95	95	3	1.6	809
										112M	200	28	FC	370	740	0	15.7	157	30	330	550	200	50	4	M12	95	95	3	1.6	834.5
32-160 40-160 65-125	50 65 80	32 40 65	80 80 100	360 360 360	132 132 132	160 160 180	24 24 24	28 30 31	30 31 33	132S	239	38	FC	370	820	0	21.9	177	20	330	650	200	50	4	M12	85	85	3	3.2	897
										80	140	19	FC	370	740	0	19.7	177	30	330	550	200	50	4	M12	95	95	3	1.1	745.5
										80M	140	19	FC	370	740	0	19.7	177	30	330	550	200	50	4	M12	95	95	3	1.1	725
										90S	156	24	FC	370	740	0	19	177	30	330	550	200	50	4	M12	95	95	3	1.1	770.5
										90L	168.5	24	FC	370	740	0	19	177	30	330	550	200	50	4	M12	95	95	3	1.1	795.5
										100L	193	28	FC	370	740	0	19.1	177	30	330	550	200	50	4	M12	95	95	3	1.6	829
										112M	200	28	FC	370	740	0	18.7	177	30	330	550	200	50	4	M12	95	95	3	1.6	854.5
										132S	239	38	FC	370	820	0	16.5	177	20	330	650	200	50	4	M12	85	85	3	3.2	917
										160M	323	42	SS	430	1000	0	41	250	110	400	660	200	50	4	M12	170	170	3	5.4	1071
										160L	345	42	SS	430	1000	0	41	250	110	400	660	200	50	4	M12	170	170	3	6.7	1115

Dimension Table for 2P Motor Drive

Pump Sizes	Pump									Motor			Base Plate							Foundation Dimensions								Coupling		Refer.
	Bore		Dimension				Axle	Weight		Frame	Dimension																			
	DN1	DN2	a	f	h1	h2	d1	Grade L	Grade R		R	d2	Mate- rial	b3	I3	A	Wt.	h3	i	b2	I2	M	N	P	Q	V1	V2	t	Wt.	TL
	mm	mm	mm	mm	mm	mm	mm	kg	kg	---	mm	mm	---	mm	mm	mm	kg	mm	mm	mm	mm	mm	mm			mm	mm	mm	kg	mm
32-200 40-200 50-160	50 65 80	32 40 50	80 80 100	360 360 360	160 160 160	180 180 180	24 24 24	36 37 32	38 39 33	90L	168.5	24	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.1	795.5
										100L	193	28	FC	370	740	0	20.4	205	30	330	550	200	50	4	M12	95	95	3	1.6	829
										112M	200	28	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.6	854.5
										132S	239	38	FC	370	820	0	20	205	20	330	650	200	50	4	M12	85	85	3	3.2	917
										160M	323	42	SS	430	1000	0	39	250	110	400	660	200	50	4	M12	170	170	3	5.4	1071
										160L	345	42	SS	430	1000	0	39	250	110	400	660	200	50	4	M12	170	170	3	6.7	1115
										180M	351.5	48	SS	430	1000	0	42	270	110	400	660	200	50	4	M12	170	170	3	9.0	1107
50-200	80	50	100	360	160	200	24	37	39	112M	200	28	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.6	854.5
										132S	239	38	FC	370	820	0	20	205	20	330	650	200	50	4	M12	85	85	3	3.2	917
										160M	323	42	SS	430	1000	0	39	250	110	400	660	200	50	4	M12	170	170	3	5.4	1071
										160L*	345	42	SS	430	1000	0	39	250	110	400	660	200	50	4	M12	170	170	3	6.7	1115
										160L**	345	48	SS	430	1000	0	39	250	110	400	660	200	50	4	M12	170	170	3	9.0	1033.5
										180MA	351.5	48	SS	430	1030	0	44	270	110	400	660	200	50	4	M12	170	200	3	9.0	1135
										180M*	351.5	48	SS	430	1030	0	44	270	110	400	660	200	50	4	M12	170	200	3	9.0	1107
										180M**	351.5	55	SS	430	1030	0	44	270	110	400	660	200	50	4	M12	170	200	4	13.9	1041
										180L	370.5	55	SS	430	1030	0	44	270	110	400	660	200	50	4	M12	170	200	4	13.9	1146
										200LA	395.5	55	SS	470	1120	0	53	292	130	440	740	200	50	4	M12	190	190	4	13.9	1234
200L	395.5	55	SS	470	1120	0	53	292	130	440	740	200	50	4	M12	190	190	4	13.9	1214.5										
80-160	100	80	125	470	160	225	32	50	52	225S	402	55	SS	530	1250	10	71	342	145	490	840	250	63	4	M16	205	205	4	13.9	1231
										132S	239	38	SS	350	1000	0	33	250	110	320	660	200	50	4	M12	170	170	3	3.2	1052
										160M	323	42	SS	430	1120	0	36	250	130	400	740	200	50	4	M12	190	190	3	5.4	1206
										160L*	345	42	SS	430	1120	0	36	250	130	400	740	200	50	4	M12	190	190	3	6.7	1250
										160L**	345	48	SS	430	1120	0	36	250	130	400	740	200	50	4	M12	190	190	3	9.0	1168.5
										180MA	351.5	48	SS	430	1180	0	46	270	130	400	740	200	50	4	M12	190	250	3	9.0	1270
										180M*	351.5	48	SS	430	1180	0	46	270	130	400	740	200	50	4	M12	190	250	3	9.0	1242
										180M**	351.5	55	SS	430	1180	0	46	270	130	400	740	200	50	4	M12	190	250	4	13.9	1176
										180L	370.5	55	SS	430	1180	0	46	270	130	400	740	200	50	4	M12	190	250	4	13.9	1281
										200LA	395.5	55	SS	470	1250	10	63	317	145	430	840	250	63	4	M16	205	205	4	13.9	1369
32-250 40-250 50-250 80-200	50 65 80 100	32 40 50 80	100 100 100 125	470 470 470 470	180 180 180 180	225 225 225 250	32 32 32 32	54 55 57 60	56 58 59 62	225S	402	55	SS	530	1250	10	65	342	145	490	840	250	63	4	M16	205	205	4	13.9	1366
										112M	200	28	FC	900	870	0	30.6	225	5	480	700	200	50	4	M12	100	100	3	3.2	989.5
										132S	239	38	FC	930	1000	0	33.9	225	0	480	740	200	50	4	M12	95	95	3	3.2	1052
										160M	323	42	SS	470	1120	0	45	270	115	440	740	200	50	4	M12	190	190	3	5.4	1206
										160L*	345	42	SS	470	1120	0	45	270	115	440	740	200	50	4	M12	190	190	3	6.7	1250
										160L**	345	48	SS	470	1120	0	45	270	115	440	740	200	50	4	M12	190	190	3	9.0	1168.5
										180MA	351.5	48	SS	470	1180	0	45	270	115	440	740	200	50	4	M12	190	250	3	9.0	1270
										180M*	351.5	48	SS	470	1180	0	45	270	115	440	740	200	50	4	M12	190	250	3	9.0	1242
										180M**	351.5	55	SS	470	1180	0	45	270	115	440	740	200	50	4	M12	190	250	4	13.9	1176
										180L	370.5	55	SS	470	1180	0	45	270	115	440	740	200	50	4	M12	190	250	4	13.9	1281
										200LA	395.5	55	SS	530	1250	10	67	317	130	490	840	250	63	4	M16	205	205	4	13.9	1369
										200L	395.5	55	SS	530	1250	10	67	317	130	490	840	250	63	4	M16	205	205	4	13.9	1349.5
										225S	402	55	SS	530	1250	10	69	342	130	490	840	250	63	4	M16	205	205	4	13.9	1366
										225MA	414.5	55	SS	530	1250	10	69	342	130	490	840	250	63	4	M16	205	205	4	13.9	1410
225M	414.5	55	SS	530	1250	10	69	342	130	490	840	250	63	4	M16	205	205	4	13.9	1463.5										
250SA	463.5	60	SS	530	1250	10	76	370	130	490	840	250	63	4	M16	205	205	4	21.0	1481.5										
250M	452.5	55	SS	530	1250	10	76	370	130	490	840	250	63	4	M16	205	205	4	13.9	1527										
80-250	100	80	125	470	225	280	32	67	70	160M	323	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	5.4	1206
										160L*	345	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	6.7	1250
										160L**	345	48	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	9.0	1168.5
										180MA	351.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1270
										180M*	351.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1242
										180M**	351.5	55	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	4	13.9	1176
										180L	370.5	55	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	4	13.9	1281
										200LA	395.5	55	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	13.9	1369
										200L	395.5	55	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	13.9	1349.5
										225S	402	55	SS	530	1250	10	65	342	115	490	840	250	63	4	M16	205	205	4	13.9	1366
										225MA	414.5	55	SS	530	1250	10	65	342	115	490	840	250	63	4	M16	205	205	4	13.9	1410
										225M	414.5	55	SS	530	1250	10	65	342	115	490	840	250	63	4	M16	205	205	4	13.9	1463.5
										250SA	463.5	60	SS	530	1250	10	74	370	115	490	840	250	63	4	M16	205	205	4	21.0	1481.5
										250M	452.5	55	SS	530	1250	10	74	370	115	490	840	250	63	4	M16	205	205	4	13.9	1527

Dimension Table

Dimension Table for 4P Motor Drive

Pump Sizes	Pump									Motor			Base Plate				Foundation Dimensions										Coupling		Refer.											
	Bore		Dimension				Axle	Weight		Frame	Dimension		Base Plate				Foundation Dimensions										Coupling													
	DN1	DN2	a	f	h1	h2	d1	Grade L	Grade R		R	d2	Mate- rial	b3	I3	A	Wt.	h3	i	b2	I2	M	N	P	Q	V1	V2	t	Wt.	TL										
	mm	mm	mm	mm	mm	mm	mm	kg	kg		mm	mm	mm	mm	mm	mm	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm										
	---	mm	mm	---	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm										
32-125 40-125	50 65	32 40	80 80	360 360	112 112	140 140	24 24	27 28	28 29	71M	120	14	FC	370	740	0	19.2	157	30	330	550	200	50	4	M12	95	95	3	1.1	681										
										80	140	19	FC	370	740	0	18.9	157	30	330	550	200	50	4	M12	95	95	3	1.1	726										
										80M	140	19	FC	370	740	0	18.9	157	30	330	550	200	50	4	M12	95	95	3	1.1	705										
32-160 40-160 65-125	50 65 80	32 40 65	80 80 100	360 360 360	132 132 132	160 160 180	24 24 24	28 30 31	30 31 33	71M	120	14	FC	370	740	0	20	177	30	330	550	200	50	4	M12	95	95	3	1.1	681										
										80	140	19	FC	370	740	0	19.7	177	30	330	550	200	50	4	M12	95	95	3	1.1	726										
										80M	140	19	FC	370	740	0	19.7	177	30	330	550	200	50	4	M12	95	95	3	1.1	705										
										90L	169	24	FC	370	740	0	19	177	30	330	550	200	50	4	M12	95	95	3	1.1	776										
										71M	120	14	FC	370	740	0	21.2	205	30	330	550	200	50	4	M12	95	95	3	1.1	701										
										80	140	19	FC	370	740	0	20.9	205	30	330	550	200	50	4	M12	95	95	3	1.1	746										
32-200 40-200 50-160 65-150	50 65 80 80	32 40 50 56	80 80 100 100	360 360 360 360	160 160 160 160	180 180 180 180	24 24 24 24	36 37 32 34	38 39 33 36	80M	140	19	FC	370	740	0	20.9	205	30	330	550	200	50	4	M12	95	95	3	1.1	725										
										90L	168.5	24	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.1	796										
										100L	193	28	FC	370	740	0	20.4	205	30	330	550	200	50	4	M12	95	95	3	1.6	838										
										112M	200	28	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.9	855										
										80	140	19	FC	370	740	0	21.7	205	30	330	550	200	50	4	M12	95	95	3	1.1	746										
										80M	140	19	FC	370	740	0	20.9	205	30	330	550	200	50	4	M12	95	95	3	1.1	725										
50-200 65-190	80 80	50 65	100 100	360 360	160 160	200 200	24 24	37 41	39 43	90L	168.5	24	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.1	796										
										100L	193	28	FC	370	740	0	20.4	205	30	330	550	200	50	4	M12	95	95	3	1.6	838										
										112M	200	28	FC	370	740	0	20.1	205	30	330	550	200	50	4	M12	95	95	3	1.9	855										
										132S	239	38	FC	370	820	0	20	205	20	330	650	200	50	4	M12	85	85	3	3.2	917										
										90L	169	24	SS	320	870	0	30	250	90	290	600	200	50	4	M12	150	120	3	3.2	906										
80-150	100	80	100	470	160	200	32	47	49	100L	193	28	SS	320	870	0	30	250	90	290	600	200	50	4	M12	150	120	3	3.2	948										
										112M	200	28	SS	320	870	0	29	250	90	290	600	200	50	4	M12	150	120	3	3.2	965										
										132S	239	38	SS	350	1000	0	33	250	110	320	660	200	50	4	M12	170	170	3	3.2	1027										
										80	140	19	FC	520	900	0	33.8	225	5	480	700	200	50	4	M12	100	100	3	3.2	881										
32-250 40-250 50-250 65-240 80-190	50 65 80 80 100	32 40 50 65 80	100 100 100 100 100	470 470 100 470 470	180 180 180 180 180	225 225 225 225 225	32 32 32 32 32	49 50 52 55 52	51 53 54 58 56	80M	140	19	FC	520	900	0	33.8	225	5	480	700	200	50	4	M12	100	100	3	3.2	860										
										90L	168.5	24	FC	520	900	0	33	225	5	480	700	200	50	4	M12	100	100	3	3.2	931										
										100L	193	28	FC	520	900	0	33.4	225	5	480	700	200	50	4	M12	100	100	3	3.2	973										
										112M	200	28	FC	520	900	0	30.6	225	5	480	700	200	50	4	M12	100	100	3	3.2	990										
										132S	239	38	FC	520	930	0	33.9	225	0	480	740	200	50	4	M12	95	95	3	3.2	1052										
										132M	258	38	FC	520	930	0	33.9	225	0	480	740	200	50	4	M12	95	95	3	5.4	1090										
										160M	323	42	SS	470	1120	0	45	270	115	440	740	200	50	4	M12	190	190	3	5.4	1206										
										100L	193	28	FC	520	900	0	34	245	5	480	700	200	50	4	M12	100	100	3	3.2	973										
										112M	200	28	FC	520	900	0	33.6	245	5	480	700	200	50	4	M12	100	100	3	3.2	990										
80-240 100-190	100 125	80 100	100 125	470 470	200 200	250 280	32 32	63 64	62 67	132S	239	38	FC	520	930	0	35	245	0	480	740	200	50	4	M12	95	95	3	3.2	1052										
										132M	258	38	FC	520	930	0	35	245	0	480	740	200	50	4	M12	95	95	3	5.4	1090										
										160M	323	42	SS	470	1120	0	49	292	100	440	740	200	50	4	M12	190	190	3	5.4	1206										
										160L	345	42	SS	470	1120	0	49	292	100	440	740	200	50	4	M12	190	190	3	6.7	1250										
										100L	193	28	FC	520	900	0	35.1	270	5	480	700	200	50	4	M12	100	100	3	3.2	948										
50-315	80	50	100	470	225	280	32	70	71	112M	200	28	FC	520	900	0	34.9	270	5	480	700	200	50	4	M12	100	100	3	3.2	965										
										132S	239	38	FC	520	930	0	36.3	270	0	480	740	200	50	4	M12	95	95	3	3.2	1027										
										132M	258	38	FC	520	930	0	36.3	270	0	480	740	200	50	4	M12	95	95	3	5.4	1065										
										160M	323	42	SS	470	1120	0	51	315	115	440	740	200	50	4	M12	190	190	3	5.4	1181										
										160L	345	42	SS	470	1120	0	51	315	115	440	740	200	50	4	M12	190	190	3	6.7	1225										
										112M	200	28	FC	520	900	0	34.9	270	5	480	700	200	50	4	M12	100	100	3	3.2	990										
100-245 100-250 65-310 80-310	125 125 80 100	100 100 65 80	125 125 125 125	470 470 470 470	225 225 225 225	280 280 280 280	32 32 32 32	71 71 76 76	75 75 72 76	132S	239	38	FC	520	930	0	36.3	270	0	480	740	200	50	4	M12	95	95	3	3.2	1052										
										132M	258	38	FC	520	930	0	36.3	270	0	480	740	200	50	4	M12	95	95	3	5.4	1090										
										160M	323	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	5.4	1206										
										160L*	345	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	6.7	1250										
										160L**	345	48	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	9.0	1169										
										180MC	351.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1270										
										180M*	351.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1242										
										180M**	351.5	55	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	4	13.9	1184										
										180LC	370.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1308										
										180L	370.5	55	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	4	13.9	1281										
										200LC	395.5	55	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	13.9	1369										
										200L*	395.5	55	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	13.9	1395										
										200L**	425.5	60	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	21.0	1380										
										100-310	125	100	125	470	250	315	32	81	91	132S	239	38	FC	520	930	0	37.7	295	0	480	740	200	50	4	M12	95	95	3	3.2	1052
																				132M	258	38	FC	520	930	0	37.7	295	0	480	740	200	50	4	M12	95	95	3	5.4	1090
160M	323	42	SS	470	1120	0	56	342	100											440	740	200	50	4	M12	190	190	3	5.4	1206										
160L*	345	42	SS	470	1120	0	56	342	100											440	740	200	50	4	M12	190	190	3	6.7	1250										
160L**	345	48																																						

Dimension Table

Dimension Table for 4P Motor Drive

Pump Sizes	Pump									Motor			Base Plate				Foundation Dimensions												Coupling		Refer.
	Bore		Dimension				Axle	Weight		Frame	Dimension																				
	DN1	DN2	a	f	h1	h2	d1	Grade L	Grade R		R	d2	Mate- rial	b3	I3	A	Wt.	h3	i	b2	I2	M	N	P	Q	V1	V2	t	Wt.	TL	
	mm	mm	mm	mm	mm	mm	mm	kg	kg		—	mm	mm	—	mm	mm	mm	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm
125-400 200-240 200-250	150 200 200	125 200 200	140 160 160	530 530 530	315 315 315	400 375 375	42 42 42	165 158 158	182 174 174	160L	345	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1263.5	
										180MC	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1365	
										180M*	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1337	
										180M**	351.5	55	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	13.9	1279	
										180LC	370.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1403	
										180L*	370.5	55	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	13.9	1376	
										180L**	400.5	60	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	21.0	1367	
										200M	406.5	65	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	21.0	1401.5	
										200LC	395.5	55	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	13.9	1464	
										200L*	395.5	55	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	13.9	1489.5	
										200L**	425.5	60	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	21.0	1474.5	
										225SC	432	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1510	
										225S*	432	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1566	
										225S**	432	65	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1491	
										225S***	432	75	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	31.0	1551	
										225MC	444.5	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1535	
										225M*	444.5	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1588.5	
										225M**	444.5	75	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	31.0	1551	
										250SC	463.5	70	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1576.5	
										250S	463.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1574	
										250MC	482.5	70	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1614.5	
										250M*	482.5	65	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	21.0	1627.5	
										250M**	482.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1652	
										280SB	544	80	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1765.5	
280S	514	75	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	31.0	1718.5											
280M*	539.5	75	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	31.0	1769.5											
280M**	569.5	85	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1777											
150-310 150-315 150-390 150-400	200 200 200 200	150 150 150 150	160 160 160 160	530 530 530 530	315 315 315 315	400 400 450 450	48 48 48 48	188 188 204 204	198 198 217 217	180MC	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1365	
										180M*	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1337	
										180M**	351.5	55	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	13.9	1279	
										180LC	370.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1403	
										180L*	370.5	55	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	13.9	1376	
										180L**	400.5	60	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	21.0	1367	
										200M	406.5	65	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	21.0	1401.5	
										200LC	395.5	55	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	13.9	1464	
										200L*	395.5	55	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	13.9	1489.5	
										200L**	425.5	60	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	21.0	1474.5	
										225SC	432	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1510	
										225S*	432	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1566	
										225S**	432	65	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1491	
										225S***	432	75	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	31.0	1551	
										225MC	444.5	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1535	
										225M*	444.5	60	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1588.5	
										225M**	444.5	75	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	31.0	1551	
										250SC	463.5	70	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1576.5	
										250S*	463.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1574	
										250S**	493.5	85	SS	640	1450	10	99	435	120	600	940	250	63	4	M16	230	280	4	45.0	1551	
										250MC	482.5	70	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1614.5	
										250M*	482.5	65	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	21.0	1627.5	
										250M**	482.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1652	
										250M***	512.5	85	SS	640	1400	10	99	435	120	600	940	250	63	4	M16	230	230	4	45.0	1606	
280SB	544	80	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1765.5											
280S*	514	75	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	31.0	1718.5											
280S**	544	85	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1726											
280MB	569.5	80	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1816											
280M*	539.5	75	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	31.0	1769.5											
280M**	569.5	85	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1777											
315SB	589	85	SS	710	1600	10	109	445	160	670	1060	250	63	4	M16	270	270	4	61.0	1855											

Dimension Table for 6P Motor Drive

Pump Sizes	Pump									Motor			Base Plate				Foundation Dimensions										Coupling		Refer.	
	Bore		Dimension				Axle	Weight		Frame	Dimension																			
	DN1	DN2	a	f	h1	h2	d1	Grade L	Grade R		R	d2	Material	b3	I3	A	Wt.	h3	i	b2	I2	M	N	P	Q	V1	V2	t	Wt.	TL
	mm	mm	mm	mm	mm	mm	mm	kg	kg		—	mm	mm	—	mm	mm	mm	kg	mm	mm	mm	mm	mm	mm			mm	mm	mm	kg
100-190	125	100	125	470	200	280	32	64	67	100L	193	28	SS	380	870	0	41	292	60	350	600	200	50	4	M12	150	120	3	3.2	972.5
										112M	200	28	SS	380	870	0	41	292	60	350	600	200	50	4	M12	150	120	3	3.2	989.5
										132S	239	38	SS	430	1000	0	46	292	80	400	660	200	50	4	M12	170	170	3	3.2	1052
										132M	258	38	SS	430	1000	0	46	292	80	400	660	200	50	4	M12	170	170	3	5.4	1090
										160M	323	42	SS	470	1120	0	49	292	100	440	740	200	50	4	M12	190	190	3	5.4	1206
										160L	345	42	SS	470	1120	0	49	292	100	440	740	200	50	4	M12	190	190	3	6.7	1250
100-245	125	100	125	470	225	280	32	71	75	112M	200	28	SS	430	870	0	45	317	60	400	600	200	50	4	M12	150	120	3	3.2	989.5
										132S	239	38	SS	430	1000	0	49	317	80	400	660	200	50	4	M12	170	170	3	3.2	1052
										132M	258	38	SS	430	1000	0	49	317	80	400	660	200	50	4	M12	170	170	3	5.4	1090
										160M	323	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	5.4	1206
										160L	345	42	SS	470	1120	0	52	317	100	440	740	200	50	4	M12	190	190	3	6.7	1250
										180M	351.5	48	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	3	9.0	1308
100-250	125	100	125	470	225	280	32	71	75	180L	370.5	55	SS	470	1180	0	55	317	100	440	740	200	50	4	M12	190	250	4	13.9	1363
										200L	425.5	60	SS	530	1250	10	74	342	115	490	840	250	63	4	M16	205	205	4	21.0	1438.5
										132S	239	38	SS	430	1000	0	51	342	80	400	660	200	50	4	M12	170	170	3	3.2	1052
										132M	258	38	SS	430	1000	0	51	342	80	400	660	200	50	4	M12	170	170	3	5.4	1090
										160M	323	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	5.4	1206
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1250
100-310	125	100	125	470	250	315	32	81	91	180M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1308
										180L	370.5	55	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	4	13.9	1363
										200L	425.5	60	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1438.5
										225S	432	65	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1479
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1250
										160M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1308
150-190	150	150	140	470	250	315	42	95	103	112M	200	28	SS	430	870	0	46	342	60	400	600	200	50	4	M12	150	120	3	5.4	1004.5
										132S	239	38	SS	430	1000	0	51	342	80	400	660	200	50	4	M12	170	170	3	5.4	1067
										132M	258	38	SS	430	1000	0	51	342	80	400	660	200	50	4	M12	170	170	3	5.4	1105
										160M	323	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	5.4	1221
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1265
										180M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1323
150-200	150	150	140	470	250	315	42	95	103	180L	370.5	55	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	4	13.9	1378
										200L	425.5	60	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1453.5
										225S	432	65	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1494
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1265
										180M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1323
										180L	370.5	55	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	4	13.9	1378
150-240	150	125	140	470	250	315	42	103	113	200L	425.5	60	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1453.5
										225S	432	65	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1494
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1265
										180M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1323
										180L	370.5	55	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	4	13.9	1378
										200L	425.5	60	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1453.5
150-250	150	125	140	470	250	315	42	103	113	225S	432	65	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1494
										160L	345	42	SS	470	1120	0	56	342	100	440	740	200	50	4	M12	190	190	3	6.7	1265
										180M	351.5	48	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	3	9.0	1323
										180L	370.5	55	SS	470	1180	0	58	342	100	440	740	200	50	4	M12	190	250	4	13.9	1378
										200L	425.5	60	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1453.5
										225S	432	65	SS	530	1250	10	75	367	115	490	840	250	63	4	M16	205	205	4	21.0	1494
125-310	150	125	140	530	280	355	42	140	151	160L	345	42	SS	530	1250	10	81	400	95	490	840	250	63	4	M16	205	205	3	6.7	1325
										180M	351.5	48	SS	530	1250	10	80	400	95	490	840	250	63	4	M16	205	205	3	9.0	1383
										180L	370.5	55	SS	530	1250	10	80	400	95	490	840	250	63	4	M16	205	205	4	13.9	1438
										200L	425.5	60	SS	590	1400	10	91	400	120	550	940	250	63	4	M16	230	230	4	21.0	1513.5
										225S	432	65	SS	590	1400	10	87	400	120	550	940	250	63	4	M16	230	230	4	21.0	1554
										250S	463.5	75	SS	590	1400	10	87	400	120	550	940	250	63	4	M16	230	230	4	31.0	1556.5
125-315	150	125	140	530	280	355	42	140	151	250M	482.5	75	SS	590	1400	10	87	400	120	550	940	250	63	4	M16	230	230	4	31.0	1651.5
										180M	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1403
										180L	370.5	55	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	4	13.9	1458
										200L	425.5	60	SS	590	1400	10	99	435	120	550	940	250	63	4	M16	230	230	4	21.0	1533.5
										225S	432	65	SS	590	1400	10	95	435	120	550	940	250	63	4	M16	230	230	4	21.0	1574
										250S	463.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1576.5
125-400	150	200	140	530	315	400	42	165	174	250M	482.5	75	SS	640	1450	10	107	435	120	600	940	250	63	4	M16	230	280	4	31.0	1671.5
										280S	544	85	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1765.5
										280M	569.5	85	SS	710	1600	10	109	435	160	670	1060	250	63	4	M16	270	270	4	45.0	1816
										180M	351.5	48	SS	590	1250	10	90	435	95	550	840	250	63	4	M16	205	205	3	9.0	1403
										180L	370.5	55	SS	590	1250	10	90	435	95											

Motor Paremeter Comparison Table by Motor Type

2P Motor

Frame size	Center height	Shaft dia.	Totally enclosed fan-cooled (TU motor)		Drip-proof		Increased-safety explosion-proof		Flame-proof	
	R	d2	Output	Weight	Output	Weight	Output	Weight	Output	Weight
---	mm	mm	kW	kg	kW	kg	kW	kg	kW	kg
71M	120	14	0.4	7	-	-	0.4	7.2	0.4	17
80	140	19	-	-	-	-	-	-	-	-
80M	140	19	0.75	18	0.75	9	0.75	11.5	0.75	26
90S	156	24	-	-	-	-	-	-	-	-
90L	168.5	24	1.5	27.5	1.5	15.5	1.5	18.5	1.5	29
100L	193	28	2.2	28	2.2	16	-	-	-	42
112M	200	28	3.7	47	3.7	27	3.7	40	3.7	58
132S	239	38	5.5	73	5.5	34	5.5	60	5.5	74
160M	323	42	11	133	11	65	7.5	85	11	125
160L*	345	42	18.5	156	18.5	105	11	115	18.5	160
160L**	345	48	-	-	22	105	-	-	-	-
180M*	351.5	48	22	235	-	-	15	150	22	205
180MA	351.5	48	-	-	-	-	-	-	-	-
180M**	351.5	55	-	-	30	120	-	-	-	-
180L	370.5	55	30	248	37	190	-	-	-	-
200LA	395.5	55	-	-	-	-	-	-	-	-
200L	395.5	55	37	333	45	357	-	-	240	345
225S	402	55	55	467	-	-	30	310	37	390
225MA	414.5	55	-	-	-	-	-	-	-	-
225M	414.5	55	-	-	-	-	-	-	45	450
250SA	463.5	60	-	-	-	-	-	-	-	-
250M	452.5	55	-	-	-	-	45	550	55	590

6P Motor


Frame size	Center height	Shaft dia.	Totally enclosed fan-cooled (TU motor)		Drip-proof		Increased-safety explosion-proof		Flame-proof	
	R	d2	Output	Weight	Output	Weight	Output	Weight	Output	Weight
---	mm	mm	kW	kg	kW	kg	kW	kg	kW	kg
100L	193	28	1.5	38	-	-	-	-	-	-
112M	200	28	2.2	46	-	-	-	-	-	-
132S	239	38	3.7	68	-	-	-	-	-	-
132M	258	38	5.5	79	-	-	-	-	-	-
160M	323	42	7.5	125	-	-	-	-	-	-
160L	345	42	11	140	-	-	-	-	-	-
180M	351.5	48	15	250	-	-	-	-	-	-
180L	370.5	55	18.5	225	-	-	-	-	-	-
200L	425.5	60	30	385	-	-	-	-	-	-
225S	432	65	45	500	-	-	-	-	-	-
250S	463.5	75	55	565	-	-	-	-	-	-
250M	482.5	75	75	640	-	-	-	-	-	-
280S	544	85	90	750	-	-	-	-	-	-
280M	569.5	85	110	725	-	-	-	-	-	-

4P Motor

Frame size	Center height	Shaft dia.	Totally enclosed fan-cooled (TU motor)		Drip-proof		Increased-safety explosion-proof		Flame-proof	
	R	d2	Output	Weight	Output	Weight	Output	Weight	Output	Weight
---	mm	mm	kW	kg	kW	kg	kW	kg	kW	kg
71M	120	14	0.4	8	-	-	0.4	9	0.4	17
80	140	19	-	-	-	-	-	-	-	-
80M	140	19	0.75	11	0.75	10.5	0.75	12	0.75	28
90L	168.5	24	1.5	20	1.5	16	1.5	20	1.5	30
100L	193	28	2.2	25	2.2	22	2.2	33	2.2	45
112M	200	28	3.7	37	3.7	30	3.7	41	3.7	58
132S	239	38	5.5	49	5.5	40	5.5	60	5.5	77
132M	258	38	7.5	60	7.5	51	7.5	74	7.5	95
160M	323	42	11	85	11	70	11	98	11	115
160L*	345	42	15	105	15	85	15	115	15	145
160L**	345	48	-	-	18.5	110	-	-	-	-
180MC	351.5	48	-	-	-	-	-	-	-	-
180M*	351.5	48	18.5	130	-	-	18.5	165	18.5	200
180M**	351.5	55	-	-	22	125	-	-	-	-
180LC	370.5	48	-	-	-	-	-	-	-	-
180L*	370.5	55	30	175	-	-	-	-	-	-
200LC	395.5	55	-	-	-	-	-	-	-	-
200L*	395.5	55	-	-	-	-	-	-	30	375
200L**	425.5	60	37	230	-	-	22	230	-	-
180L**	400.5	60	-	-	37	195	-	-	-	-
225SC	432	60	-	-	-	-	-	-	-	-
225S*	432	60	-	-	-	-	-	-	37	440
225S**	432	65	55	275	-	-	30	295	-	-
200M	406.5	65	-	-	55	240	-	-	-	-
225MC	444.5	60	-	-	-	-	-	-	-	-
225M	444.5	60	-	-	-	-	-	-	45	500
250SC	463.5	70	-	-	-	-	-	-	-	-
250M*	482.5	65	-	-	-	-	-	-	55	600
250M**	482.5	75	90	520	-	-	45	550	-	-
225S	432	75	-	-	75	350	-	-	-	-
225M	444.5	75	-	-	90	380	-	-	-	-
250S	463.5	75	75	470	-	-	-	-	-	-
250MC	482.5	70	-	-	-	-	-	-	-	-
280SB	544	80	-	-	-	-	-	-	-	-
280S*	514	75	-	-	-	-	-	-	75	780
280M*	539.5	75	-	-	-	-	-	-	90	920
280M**	569.5	85	132	800	-	-	75	800	-	-
250S	493.5	85	-	-	110	500	-	-	-	-
250M***	512.5	85	-	-	132	565	-	-	-	-
280S**	544	85	110	685	-	-	-	-	-	-
280MB	569.5	80	-	-	-	-	-	-	-	-
315SB	589	85	-	-	-	-	-	-	-	-

Potential Energy Saving with the Eco-Pump

The Eco-Pumps reduce power consumption by 10~30%!




The above figures are a few examples of successfull installation of the Eco-Pumps in various industries.

6 typical examples where big engery savings can be expected:

- Pump flow rate controlled by valve
- Pump operating at fixed speed
- Pump with high annual operating hours
- Pump with oversized motor
- Old pump
- Pump for new facility

We propose several solutions depending on your situation:



Would you like to try to select an Eco-Pump that meets your requirements, look at testimonials, or just learn more about the Eco-Pumps?
Then please visit the Eco-Pump website:
www.torishima.co.jp/en/ecopump/index.html



Note: Totally eclosed fan-cooled motor is only available for TU motor, Torishima Ultra motor.